BATA INDUSTRIALS
FORWARD

GOAL W–XW







BASIC INFORMATION

Article no.	M3LP0PE3310 (W) M3LP0PE3311 (XW)
Safety category	S3S
Standard	EN ISO 20345:2022+A1:2024 S3S FO SR SC / ESD EN 61340-4-3:2002 Class 1
DGUV	Yes
Model	Low cut
Country of origin	NL

SIZE RANGE

Width	FR	UK
W	36-49	3-14
XW	38-48	5-13

DESCRIPTION

Goal is an S3S, full metal-free, lightweight safety shoe. The Walkline® technology guides your feet's contact with the ground for the most ergonomic walking gait. This results in better energy retention, so less fatigue throughout and at the end of the workday.

RECOMMENDED FOR

Automotive
Facilities
Light Industry
Transport & Logistics

MATERIAL PROPERTIES

Safety toecap	Polyamide
Perforation-resistant insert	FlexGuard® non-metallic insert
Upper	Microfiber
Midsole	Bio-based PU
Outsole	Bio-based PU
Inlay sole	Premium Fit 85% GRS POLIYOU® foam
Insole	FlexGuard® non-metallic insert
Lining	Polyester
Closure	Laces, Polyester, 100 cm
Scuff cap	TPU
Shank	2 density shank

SAFETY FEATURES

ESD – EN 61340-4-3:2002 Class 1
CI – Cold insulation
E – Energy absorption of seat region
FO – Fuel and oil resistant outsole
HI – Heat insulation
PS – Non-metal insert resistant to nails down to ø 3.0 mm
SC – Abrasion resistant scuff cap
SR – Slip resistance
WPA – Water penetration and absorption resistant upper

FEATURES AND TECHNOLOGIES

Heel grip
Dual density sole
Bata Cool Comfort® lining with Odor Control
Metal-free

CERTIFIED WITH INLAY SOLES

Premium Fit
Superior Fit
Excellent Fit
Medical Fit Heel
Medical Fit Forefoot
Bata orthopaedic inlay soles

CERTIFICATIONS

PARTNERS

POLIYOU® POWERED BY KUN HUANG

PACKAGING

	36–46	47–49
Gross weight (pair) (kg)	1.38	
Net weight (pair) (kg)	1.17	
Unit package L×W×H (mm)	358×192×126	358×230×126
Units per carton	10	10
Carton L×W×H (mm)	655×400×372	655×472×372
Units per container 20 foot	2300 - 2500	
Units per container 40 foot	5200 - 5400	
Units per container 40 foot HQ	6000 - 6300	